

MURACRIL 116 EE (extra external) QUARTZ WALL PAINT
FOR INTERIOR / EXTERIOR ANTI-ALGAE - ANTI-MOULD

Characteristics

High quality water-based wall paint for interiors / exteriors based on unsaponifiable synthetic resins, selected pigments resistant to degradation and quartzes with selected granulometry.
It can be applied very easily with a brush, roller or spray even on large surfaces.

It has a high yield and strong coverage so that it covers any shade with just two coats. It leaves no lapping defects.

The quartz Muracril 116 EE where the quartz has a reinforcing function, allows to obtain coatings with excellent filling and with remarkable decorative effects for external facades and internal walls, suitable for any climatic situation.

The product does not contain substances classified as harmful.

Principles of photocatalysis: Thanks to the use of titanium dioxide in the formula which, when subjected to sunlight, the molecules of polluting substances are transformed into substances harmless to health, and the process is also activated in the presence of artificial light.

Binder : Acrylic

I wait : Rough matte

Washability : After 48 hours. 10,000 brush strokes

Specific weight : 1,550 – 1,600 kg / l

Viscosity at 20°C. : 15,000 - 17,000

Surrender : **By brush** : dilution with water 25% by volume - 9 m²/l (2 coats)
: **By roller** : dilution with water 25% by volume - 9 m²/l (2 coats)
: **By spray** : dilution with water 30% by volume -14 m²/l (1 coat)

Color : White.

Drying : To the touch : 40 minutes
Stackability : 6 hours

VOC classification : EU limit value for this product (Cat.A/a): 30 g/l (2010)
(Directive 2004/42/EC) : This product contains a maximum of 30 g/l of VOC