



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

MURACRIL 116 EE (extra external) with QUARTZ WATER-BASED WALL PAINT FOR INTERIOR / EXTERIOR ANTI-ALGAE - ANTI-MOLD

Features	<p>High quality water-based wall paint for interiors / exteriors based on unsaponifiable synthetic resins, selected pigments resistant to degradation and selected granulometry quartz.</p> <p>It is extremely easy to apply by brush, roller or spray even on large surfaces.</p> <p>It has a great yield and strong coverage so that with just two coats it covers any color.</p> <p>The Muracril 116 EE quartz where the quartz acts as a reinforcement, it allows to obtain coatings with excellent filling and with remarkable decorative effects for external facades and internal walls, suitable for any climatic situation.</p>	
Principles of photocatalysis	<p>The product does not contain substances classified as harmful.</p> <p>: In the formula, thanks to the use of titanium dioxide which, subjected to sunlight, the molecules of pollutants are transformed into substances harmless to health, and the process is also activated in the presence of artificial light.</p>	
Binder	: Acrylic	
Appearance	: Rough matte	
Washability	: After 48 hours.	10,000 brush strokes
Specific weight	: 1,550 - 1,600 kg / l	
Viscosity at 20 ° C.	: 15,000 - 17,000	
Surrender	<p>: <u>Perfect fit</u> : dilution with water 25% by volume - 9 m² / l (2 coats):</p> <p>: <u>By roller</u> : dilution with water 25% by volume - 9 m² / l (2 coats):</p> <p>: <u>Spray</u> : dilution with water 30% by volume - 14 m² / l (1 coat)</p>	
Color	: White.	
Drying	<p>: To the touch : 40 minutes</p> <p>Overlap : 6 hours</p>	
VOC classification (Directive 2004/42 / EC)	: EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC	