



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

MUROXAN

SILOXANE WATER-BASED PAINT FOR EXTERIORS

Product features

Water-based paint for facades based on siliceous polymers (siloxanes) and inorganic pigments.

Ideal paint for historic buildings, with very high breathability, excellent water repellency to rain, prevents the proliferation of algae and mold, is hardly dirty and is absolutely easy to apply.

Specific weight

About 1,600 kg / l white About
1,4 - 1,5 kg / l colored Minimum

Theoretical consumption

0.150 l / m² per coat Dry to

Drying times

touch: after 3 hours Dry: after 6
hours

Recoatable: at least after 6 hours

: maximum no limitation

Support conditions

Mineral substrates: clean and dry, pre-treated with MUROXANFIX, then apply 2 finishing coats of MUROXAN.

NB carry out the applications when the temperature of the environment and / or of the substrate is between 5 and 30 ° C.

Instructions for Use

Mix the product thoroughly before use.

Application

Roller / brush

Air spray

Airless spray

Recommended thinner

Waterfall

Waterfall

Waterfall

Volume of the diluent

0 - 5%

10%

10%

Diameter of the nozzle

-

2 mm

0.53-0.68mm Pressure

to the nozzle

-

3-4atm

150 atm

Color

White

Storage life (in a cool and dry place)

Minimum 12 months.



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

VOC classification
(Directive 2004/42 / EC)

: EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC