



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

FONDO PLUS

HIGH PENETRATION WATER-REPELLENT WHITE PIGMENTED INSULATOR CONSOLIDATING

Employments : As a base - insulating, for plasterboard - masonry. The particle size, less than 1 micron, allows a deep penetration into the pores and consequently a better consolidation of the supports. The uniformity of the surfaces guarantees better finishes. High resistance to alkali. Excellent for insulating gypsum, plasterboard and concrete substrates, to be covered with wallpaper and whitewashed with water-based paints.

CHEMICAL - PHYSICAL CHARACTERISTICS

Specific weight	: 1,380 - 1,410 kg / lt
Viscosity at 20 ° C	approximately: 7000 - 7500
Binder	: Organosol styrene-acrylic: to
Drying	the touch 40 minutes
Overpaintable	: after 6 hours

Packaging : lt 25 - 5 - 1

Color : White

Surrender : Approx. 6 - 8 sqm / lt (with 2 coats) depending on the absorption of the substrate.

VOC classification : EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC
(Directive 2004/42 / EC)

APPLICATION PROCEDURE

: By brush or roller after dilution with 30-% water, by spray 40%

Warnings : Protect from frost; do not apply at temperatures below + 10 ° C. Keep out of reach of children, do not eat, drink and / or smoke during use. Store in a cool, dry and frost-free place.