



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

## DATA SHEET

### QUARZOPLASTER

#### ROUGH TEXTURED PLASTIC

<b>Features</b>	Continuous pigmented plastic coating based on selected quartz and high-quality synthetic resin in emulsion. It allows to obtain very hard and very elastic peeled surfaces, water-repellent but transpiring, lasting in any climate and endowed with remarkable aesthetic value.
<b>Application procedure</b>	The substrate temperature must be above 10 ° C. The application must not be started in the presence of beating sun, wind, dust, fumes.
<b>Binder</b>	Synthetic copolymer in aqueous emulsion
<b>Pigments</b>	Non-toxic according to EEC standards
<b>Appearance</b>	Dull, rough peel
<b>Washability</b>	Over 10,000 brush strokes
<b>Specific weight</b>	1,700 kg / l
<b>Surrender</b>	Depending on the roughness of the substrate and the desired thickness, from 800 grams to 2 kg / m <sup>2</sup>
<b>Drying</b>	Complete drying in depth is achieved after 24 hours under normal conditions
<b>Color</b>	White
<b>Viscosity</b>	Thixotropic
<b>VOC classification (Directive 2004/42 / EC)</b>	: EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC