



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it-email: info@lakplaster.it

DATA SHEET

TITANSUPER

BREATHABLE WALL PAINT FOR INDOOR OUTDOOR

Characteristics	emulsion and special microniz a partially water-repellent and therefore it can also be used in TITANSUPER can be used out	tor exteriors based on fine synthetic resins in teed fillers coated with wax. This makes TITANSUPER highly breathable paint. it is a thixotropic product in high thicknesses without the risk of sagging. Adoors, but not on walls directly exposed to rain foof and free from substances classified as harmful.
Binder	: Synthetic copolymer in aqueous emulsion	
l wait	: Opaque	
Washability	: After 48 hours. 6000 Brush strokes	
Specific weight	: 1,660 – 1,680 kg / l	
Viscosity at 20°C.	: 14,500 - 16,000	
Surrender	: By brush : di lution with water 20% by volume - 7 m2/l (2 coats) : dilution with <u>By rolle</u> r water 20% by volume - 7 m2/l (2 coats) By spray: d ilution with water 30% by volume - 10 m2/l (1 coat)	
Color	: White.	
Drying	: to the touch Stackability	: 35 minutes : 6 hours

VOC classification : EU limit value for this product (Cat.A/a): 30 g/l (2010) (Directive 2004/42/EC) : This product contains a maximum of 30 g/l of VOC