



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - email: info@lakplaster.it

**DATA SHEET** 

## ANTI-STAIN WATER PAINT

## WATER-BASED ANTI-STAIN AND ANTI-NICOTINE WATER-BASED PAINT

Characteristics Special water-based paint for interior walls. The product is

applied in two or three coats without leaves no lapping defects, and has the function of isolating stains caused by nicotine contamination, halos, coffee and tea stains, soot, smoke and mould. Can be applied to plaster, concrete, drywall, brick, wallpaper and fiberglass wall fabrics. The product is fireproof

and non-toxic.

Binder : Acrylic

I wait : Opaque

Washability : After 48 hours over 10,000 brush strokes without defects

Specific weight : about 1,480 kg/l

Viscosity at 20°C : 19,000 - 23,000

Surrender By brush: dilution with water 5% by volume - 8 m2/l (2 coats) by roller:

dilution with water 5% by volume - 8 m2/l (2 coats) by spray: dilution with

water 7% by volume - 10 m2/l (1 coat)

Color : White.

Drying : To the touch : after 1 hour :

Overpaintable with Muracril 106 after 4 hours

VOC classification: EU limit value for this product (Cat.A/a): 30 g/l (2010) (Directive 2004/42/EC): This product contains a maximum of 30 g/l of VOC