

ACRYLAK 092 / D

**TRANSPARENT GLOSSY WATER-BASED WATER-REPELLENT ANTI-SCRATCH PAINT
FOR INDOOR - OUTDOOR**

Characteristics

Transparent glossy varnish based on special resins emulsified in water. After drying, the film has high fullness, excellent behavior outdoors and considerable resistance to water and weak alkalis. Acrylak 092/D can be diluted with water to various extents, which allows the degree of gloss of the finish to be varied according to requirements. The product is fireproof and free from substances classified as harmful.

The smell is very faint, and therefore its use even in closed and confined environments does not present any difficulty. It leaves no lapping defects.

Jobs

: As a polish for wall models or masonry supports, when excellent resistance to bad weather and perfect transparency are required.

As a polisher for iron, wood, walls, waterproofing for porous substrates (paper, terracotta, cement, pre-compressed aggregates, etc.), when a good seal against humidity is required.

Binder

: Synthetic styrene-acrylic in aqueous emulsion

l wait

: Glossy transparent

Washability

: After 15 hours. 10,000 brush strokes

Walkability

: After 24 hours

Specific weight

: 1.00 - 1.04 kg / l

Surrender

: Varies according to the type of support, from 3 m²/lt to 10 m²/lt

Viscosity at 20°C

: 6,500 – 8,000

Packaging

: 25 - 5 - 1 liters

**VOC classification : EU limit value for this product (Cat.A/a): 30 g/l (2010)
(Directive 2004/42/EC) : This product contains a maximum of 30 g/l of VOC**