



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

TITANSUPER

BREATHABLE WALL PAINT FOR INTERIOR EXTERIOR

Features	Breathable wall paint for internal and external use based on high-quality synthetic resins in emulsion and special micronized fillers coated with wax. This makes it <i>TITANSUPER</i> a partially water-repellent and very breathable paint. It is a thixotropic product therefore it can also be used at high thicknesses without the risk of sagging. The <i>TITANSUPER</i> it can be used for exteriors, but not on walls directly exposed to rain washout. The product is fireproof and free from substances classified as harmful.	
Binder	: Synthetic copolymer in aqueous emulsion	
Appearance	: Opaque	
Washability	: After 48 hours. 6000 Brush strokes	
Specific weight	: 1,660 - 1,680 kg / l	
Viscosity at 20 ° C.	: 14,500 - 16,000	
Surrender	: <u>Perfect fit</u> : dilution with water 20% by volume - 7 m ² / l (2 coats) <u>By roller</u> : dilution with water 20% by volume - 7 m ² / l (2 coats): <u>Spray</u> dilution with water 30% by volume - 10 m ² / l (1 coat)	
Color	: White.	
Drying	: to the touch	: 35 minutes
	Overlap	: 6 hours
VOC classification (Directive 2004/42 / EC)	: EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC	