



**Lak Plaster**®  
PITTURE E VERNICI



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

## DATA SHEET

### LAKOPAC

#### THIXOTROPIC FILLING UNDERGLASS FOR IRON - WOOD - WALL

#### **Features**

: Undercoat for universal use based on alkyd resins. Equipped with a remarkable consistency, covering and elasticity, it effectively covers the porosity of the wood on which it acts as a clinging sealer, and is And particularly suitable on wall supports yellowed by nicotine, coffee and on yellow stains caused by infiltration and soot; it constitutes in any case (even on iron after applying an antirust) an ideal preparation coat for any synthetic, oleosynthetic or greasy enamel both inside and outside; finally excellent as a first coat on cast iron radiators as it is very filler.

*Lakopac*, being of low specific weight, it is of high yield and considerable coverage. Easy to apply and excellent sanding, it resists for a long time outdoors even if exposed to the elements without the protection of the finishing coat: it therefore advantageously replaces, both from a technical and economic point of view, all the most current old paints used up to now for the preparation of funds.

#### **Appearance**

: Semi-opaque

#### **Specific weight**

: 1,500 - 1,550 kg / lt

#### **Application**

: By brush or spray

#### **Dilution**

: Perfect fit 10 - 12% with white spirit

: Spray 15 - 18% with white spirit

#### **Surrender**

: Perfect fit : 10 - 12 sqm / lt

Spray : 9 - 10 sqm / lt