



# Lak Plaster®

PAINTS AND VARNISHES

21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

## DATA SHEET



### CRISTAL-PLAST® Temporary protective paint

#### Property :

Cristal Plast® is a water-soluble synthetic paint for interiors and exteriors. It forms an elastic, non-slip, aponic plastic film that has temporary protection characteristics from scratches and bad weather, also useful as an insulator for electrical components; the dry film can be easily removed from the supports. Cristal Plast® is applied to all materials, in particular painted metals and plastics, provided that the surfaces are smooth and free from porosity.

#### Fields of use:

- . As protective layers on spray booths, bodywork, cars, glass, marble.
- . As a temporary protection against spray droplets, against mechanical stresses (transport, storage, assembly), dirt, chemicals or cleaning agents, against the influence of bad weather (corrosion) etc. on the most diverse objects.

#### Preparation:

The substrate must be smooth, dry, solid and free from grease and grease. Do not apply below 8 ° C.

#### Application system:

Cristal Plast can be applied by brush, roller, spray (with nozzle Ø 1.9-4 in this case it is recommended to dilute the product from 10 to 25% with mains water), and by immersion.

Homogenize the product before use.

The application must be rather abundant because with a too thin layer the paint is difficult to remove.

Clean the equipment immediately after use with water or a mixture of water and detergent.

#### Drying:

- . Touch dry after 60/70 minutes
- . It can be subjected to stress after at least 4/5 hours (depending on temperature, air humidity and layer thickness).

#### How to use:

The product can be used as it is or diluted with water from 5 to 15%

#### Surrender:

- . 5-8 m<sup>2</sup> per kg approx
- . with a thickness of 200 microns when wet and 150 microns when dry

#### Packaging:

- . From 25 kg, 5 kg, 1 kg





21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

[www.lakplaster.it](http://www.lakplaster.it) - e-mail: [info@lakplaster.it](mailto:info@lakplaster.it)

## DATA SHEET

### Storage:

The product can be kept for at least 8 months in its original, tightly closed packaging. Protect from the cold.

**Appearance:** semilucid

**Viscosity:** 4000 + -300 mPa.s

**Specific weight :** 1,050 Kg / l (colorless) 1,100 Kg / l (colored)

**Colors:** colorless, white, black, blue ral 5015, sample colors on request

### Classification and handling:

For information on chemical properties and risks, as well as the requirements for transport, handling, storage, disposal, etc., consult the safety data sheet. **Remarks:**

This data sheet is considered as a directive or advice without any obligation. The application must be adapted to the relevant conditions. For specific cases, consult our technical service.