



Lak Plaster[®]
PITTURE E VERNICI



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

PLASTOLAK

SMOOTH TEXTURED PLASTIC WITH DIRECT GLOSS FOR INTERIORS

- Features** : Continuous pigmented plastic coating with high coverage power and a mixture of concentrated and stabilized synthetic resins in emulsion. The dried product is brilliant, therefore it speeds up processing times by eliminating the next coat of (clear or enamel) and also significantly reduces the cost of application. It has a high mechanical resistance, easy to clean and resists washing. The product is fireproof and non-toxic.
- Application procedure** : The substrate temperature must be above 10 ° C:
The application must be that of a normal model.
- Binder** : Styrolacrylic in aqueous emulsion.
- Pigments** : Non-toxic according to EEC standards
- Appearance** : Glossy peel
- Washability** : After 48 hours. 15,000 Brush strokes
- Specific weight** : 1,150 - 1,250 kg / lt
- Surrender** : Depending on the desired skin relief and the roughness of the support, from 500 Gr. to 1 kg / m2
- Drying** : Touch dry after 8 hours under normal temperature conditions and humidity of the air.
- Colors** :White
- storage** : Plastolak can be stored for up to 12 months in original containers as long as it is kept in stock at temperatures between 5 ° and 30 ° C. The product cannot stand freezing.
- Hazard class** : Exempt - non-flammable
- VOC classification** : EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC
(Directive 2004/42 / EC)