



Lak Plaster[®]
PITTURE E VERNICI



21042 CARONNO PERTUSELLA (Va) – Via Trieste 285 – Tel. 029650607 – Fax 029659754

www.lakplaster.it – email: info@lakplaster.it

DATA SHEET

FUND PLUS

**HIGH PENETRATION WATER-REPELLENT WHITE PIGMENTED INSULATION
CONSOLIDATING**

Jobs : As a primer - insulator, for plasterboard - masonry works. The size of the particles, less than 1 micron, allows a deep penetration into the pores and consequently a better consolidation of the substrates. The uniformity of the surfaces guarantees better finishes. High resistance to alkalis. Excellent for insulating gypsum, plasterboard and cement substrates, to be covered with wallpaper and whitewashed with water-based paints. It leaves no lapping defects.

CHEMICAL - PHYSICAL CHARACTERISTICS

Specific weight	: 1,380 - 1,410 kg/ l approx. :
Viscosity at 20°C	7000 - 7500
Binder	: Styrene-acrylic organosol :
Drying	to the touch 40
Overpaintable	minutes : after 6 hours

Packaging : l 14 - 5

Color : White

Surrender : 6 - 8 m²/lt approximately (with 2 coats) depending on the absorption of the support.

VOC classification : EU limit value for this product (Cat.A/a): 30 g/l (2010)
(Directive 2004/42/EC) : This product contains a maximum of 30 g/l of VOC

APPLICATION PROCEDURE

: By brush or roller after dilution with water 30- %, by spray dilution 40% : Keep away from frost;

Warnings do not apply at temperatures below +10°C.
Keep out of reach of children, do not eat, drink and / or smoke when using.
Store in a cool, dry and frost-free place.