



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - email: info@lakplaster.it

DATA SHEET

MURACRIL 106 PLUS

WALL PAINTING FOR INTERIORS AND EXTERIORS

Characteristics : High quality water-based wall paint for interiors and exteriors based on

emulsified synthetic resins. It can be applied very easily with a brush, roller or spray even on large surfaces. It has a high yield and strong coverage, so with

just two coats it covers any shade.

It allows to obtain wall coverings for external facades and internal walls that are washable and resistant to any climate; of remarkable decorative effect fullness

and uniformity of colour. It leaves no lapping defects.

The product is free from substances classified as harmful.

Principles of photocatalysis: In the formula, thanks to the use of titanium dioxide which, subjected to sunlight,
the molecules of polluting substances are transformed into substances harmless
to health, and the process is also activated in the presence of artificial light.

Binder : Acrylic

I wait : Opaque

Washability : After 48 hours. 12,000 brush strokes

Specific weight : 1,520 – 1,550 kg / I

Viscosity at 20°C : 14,000 - 16,000

Surrender : By brush : dilution with water 30% by volume - 9 m2/l (2 coats)

By roller: dilution with water 30% by volume - 9 m2/l (2 coats)
By spray: dilution with water 40% by volume - 13 m2/l (1 coat)

Color :White

Drying : To the touch : 40 minutes

Stackability: 6 hours

VOC classification: EU limit value for this product (Cat.A/a): 30 g/l (2010) (Directive 2004/42/EC): This product contains a maximum of 30 g/l of VOC