



Lak Plaster®
PITTURE E VERNICI



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

N / 724

FIXING INSULATION FOR INTERNAL EXTERNAL WALL

Features	: Aqueous emulsion of special acrylic copolymer with excellent resistance to water and weak alkalis, remarkable insulating and fixing power for absorbent wall surfaces. The product is fireproof and non-toxic.
Employments	: As a fixative insulator for masonry works, to which it gives particular uniformity of absorption, optimally preparing the surfaces for subsequent applications of paints or water-based or solvent-based plastic coatings.
Supports	: All masonry works inside or outside.
Binder	: Acrylic copolymer
Specific weight	: 1,000 kg / lt
Surrender	: 8 - 10 sqm / lt depending on the absorption of the substrate
Viscosity	: 15 sec ford cup 4 at 25 ° C
Packaging	: lt 20 - 5 - 1

APPLICATION PROCEDURE

: By brush or wool roller after diluting 1: 6 with water

VOC classification
(Directive 2004/42 / EC) : EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC