



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

## DATA SHEET

### ACRILAK 092 / D

WATER-BASED SHINY, WATER-REPELLENT, ANTI-SCRATCH PAINT  
FOR INTERNAL - EXTERNAL

#### **Features**

Transparent glossy varnish based on special resins emulsified in water. After drying, the film is endowed with high fullness, excellent outdoor behavior and remarkable resistance to water and weak alkalis. *Acrilak 092 / D* it can be diluted with water to varying degrees, which allows you to vary the degree of gloss of the finish, according to your needs. The product is fireproof and free from substances classified as harmful.

The smell is very faint, and therefore its use even in closed and confined environments, does not present any difficulty.

#### **Employments**

: As a polishing agent for wall plastics or masonry substrates, when excellent weather resistance and perfect transparency are required.

As a waterproofing polisher for porous substrates (paper, terracotta, concrete, prestressed aggregates, etc.), when good resistance to humidity is required.

#### **Binder**

: Synthetic styrene-acrylic in aqueous emulsion

#### **Appearance**

: Glossy clear

#### **Washability**

: After 20 hours. 10,000 brush strokes

#### **Walkability**

: After 48 hours

#### **Specific weight**

: 1.00 - 1.04 kg / l

#### **Surrender**

: Varies according to the type of substrate, from 3 sqm / lt to 10 sqm / lt

#### **Viscosity at 20 ° C**

: 8,000 - 12,000

#### **Packaging**

: 25 - 5 - 1 liters

#### **VOC classification** **(Directive 2004/42 / EC)**

: EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC