

TRANSPARENT SATIN WATER IMPREGNATING AGENT - COLOURED

ACRYLIC FINISH WITH WAXY WATER

| | |
|-----------------------------|--|
| Characteristics | Impregnated with transparent and coloured protective water finish, professional use, based on special acrylic resins. Suitable for the ultimate protection of chalets, perlinature, window frames, doors, fences, under-roofs and in general for each wood covering internal or external. Compared to thixotropic finishes it is easy Brush and roller application, in spray applications is It is advisable to make thinner layers. |
| Field of application | : Especially designed for brush application on artifacts where a softness to the touch and an effect similar to the wax. |
| Color | : Transparent - coloured |
| Binder | : Acrylic |
| Specific gravity | : 1,000 kg/litre |
| Viscosity | Price: 25 cup Ford 4 |
| Dilution | With water, from 2 to 5 |
| Application | : Roller mohair , flat brush with synthetic fibres for water, spray equipment. Clean the equipment with water, immediately after use |
| Drying | Dry to the touch after about 3 hours; cold and high humidity increase the drying time. Stackability after 5 - 7 hours Do not apply with temperature below + 10 °F and with humidity Air is greater than 75%. |
| Surrender | : 5 - 7 square meters with 1 liter (2 hands) |
| Storage | The product must be stored in its original containers, frost protection and a minimum temperature of + 5 °C and max + 35 C. The product has a stability of 12 months. |



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

Classification VOC (Directive 2004/42/EC) : EU limit value for this product (Cat.A/a): 30 g/l (2010)
This product contains a maximum of 30 g/l VOC