

IDROLAK

VERSATILE WATER-BASED ENAMEL FOR INDOOR OUTDOOR

Characteristics	IDROLAK is an enamel based on synthetic acrylic resins, dilutable with water, resistant to atmospheric agents, particularly suitable for painting wooden supports, concrete, fiber cement walls, rigid PVC, iron. IDROLAK stands out for its high resistance to bad weather, it has permanent elasticity, it does not yellow, it is resistant to light, particularly odorless it is easy to apply, it dries quickly so that if necessary up to three coats a day can be applied, and it leaves no lapping defects. IDROLAK complies with the EURO EN 71 toy safety standard and with the DIN 53 160 standard resistant to saliva and perspiration.
Field of use	: All supports in wood, iron, concrete, walls, fiber cement (after adequate preparation), rigid PVC, toys.
Aesthetic effect	: IDROLAK is available in the Glossy/ Satin (about 20 gloss)/ Matt (about 8 gloss) versions
Viscosity at 20°C	4000 – 6000
Specific weight	: 1,200 – 1,250 approximately depending on the colour
Dilution	: With water, 0 to 8%
Application	: Mohair roller, flat brush with synthetic fibers for water-based enamels, spray equipment. Clean equipment with water immediately after use
Drying	: Dry to the touch, after about 2 hours; cold and high humidity increase the drying time. Do not apply at temperatures below +10°C and with air humidity above 75%.
Binder	Acrylic polyurethane
Surrender	: 7 - 8 square meters with 1 litre (2 hands)



21042 CARONNO PERTUSELLA (Va) – Via Trieste 285 – Tel. 029650607 – Fax 029659754

www.lakplaster.it – email: info@lakplaster.it

DATA SHEET

**VOC classification : EU limit value for this product (Cat.A/a): 30 g/l (2010)
(Directive 2004/42/EC) : This product contains a maximum of 30 g/l of VOC**