



**Lak Plaster**®  
PITTURE E VERNICI



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

## DATA SHEET

### TERMOLAK® ANTI-CONDENSATION ANTI-MOLD

#### WASHABLE WATER-BASED PAINT FOR INTERIORS

#### **Features**

: Washable water-based paint for internal action Anti-condensation formula are Anti-mold, because in the present some microspheres and a particular type of fungicide.

This makes it advisable TERMOLAK® by community, men - if, pantries, where mold, blackening and other problems caused by condensation can develop due to the presence of food products in a humid environment.

TERMOLAK® creates the "double glass" type insulating effect due to the cavities of the microspheres and their very low thermal conductivity, and also develops a visu thermal insulating action to be realized by a warm and soft sensation to the touch.

The maximum performance of the product is obtained by applying a thickness of approximately 100 microns to the substrate, equivalent to 2 or more coats.

Finally, it is noted that the product is totally fireproof and non-toxic.

#### **Binder**

: Acrylic

#### **Appearance**

: Opaque

#### **Specific weight**

: 0,900 kg / lt

#### **Viscosity at 20 ° C**

: 30,000 - 32,000

#### **Yield / Application:**

By brush (recommended for civil plasters)

dilution with water 20-30% 3 sqm / lt 3 coats

By roller (short hair) (recommended for civil and gypsum plaster)

dilution with water 20-30% 4 sqm / lt 3 coats

#### **Washability**

: after 48 hours. 6000 brush strokes

#### **Color**

: White.

#### **Drying**

: To the touch : 60 minutes

Overlap : 8 hours



**Lak Plaster**®  
PITTURE E VERNICI



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

## DATA SHEET

### **Usage:**

#### **NEW WALLS**

: brush the surface to remove any dust or residue not anchored to the support. Isolate the wall with ISOLAK diluted 1/1, apply TERMOLAK® the first coat diluted at 20% after 5 hours apply the second coat diluted at 20%.

#### **OLD WALLS**

: brush and wash thoroughly with water to remove everything that is not firmly anchored to the plaster or that is not resistant to water, where mold appears, wash it with water and 1/5 diluted bleach; if the walls are already whitewashed, it is necessary to insulate the wall with ISOLAK diluted 1/1, then apply TERMOLAK®

#### **VOC classification** **(Directive 2004/42 / EC)**

: EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC