



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

GRANPLASTER

RUSTIC PLASTIC VENICE TYPE FOR EXTERIOR - INTERIOR

Features	Continuous pigmented plastic coating based on selected quartz, marble grit and precious synthetic resin in emulsion, stabilizing additives and fungicides; totally fireproof and non-toxic
Binder	Synthetic copolymer in aqueous emulsion
Pigments	Non-toxic according to EEC standards
Appearance	Matte, rustic
Dry residue at 105 ° C	: 72 ± 1%
Dry residue at 450 ° C	: 70%
Washability	: Over 8000 brush strokes
Specific weight	about 1,700 kg / lt
Granulometry	1 - 1.2 mm
Surrender	Depending on the roughness of the substrate 2 - 3 kg / m2
Hardening	Complete drying in depth is obtained after 48 hours at medium temperature.
Color	White.
Application procedure	The substrate temperature must be above 10 ° C. The application must not be started in the presence of wind, dust, fumes.
storage	Granplaster can be stored for up to 12 months in a closed bucket, as long as it is kept in stock at temperatures between 0 ° and 30 ° C. The product cannot stand freezing.
VOC classification (Directive 2004/42 / EC)	: EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC