



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

TRANSPARENT IDROLAK

WATER-BASED WAXY SATIN FINISH

Features	IDROLAK TRASPARENTE DI FINITURA water-based is a satin transparent protective varnish for professional use, based on special acrylic resins. Suitable for the definitive protection of chalets, matchboards, window frames, doors, fences, attics and in general for any internal and external wooden cladding. Compared to thixotropic finishes it is easy to apply by brush and roller, in spray applications it is advisable to make thinner layers.
Field of use	: Particularly designed for application on wood and artefacts where a softness to the touch and a waxy effect are required.
Aesthetic effect	: Transparent - satin
Viscosity at 20 ° C	: 1500 - 2000
Specific weight	: 1,030 - 1,070 kg / lt
Dilution	: With water, 0 to 8%
Application	: Mohair roller, flat brush with synthetic fibers for water-based enamels, spray equipment. Clean equipment with water immediately after use
Drying	: Touch dry, after about 2 hours; cold and high humidity increase the drying time. Do not apply at temperatures below + 10 ° C and with air humidity above 75%.
Binder	: Acrylic
Surrender	: 7 - 8 square meters with 1 liter (2 coats)
Storage	: The product must be stored in its original containers, protected from frost and at a minimum temperature of + 5 ° C and max + 35 ° C. The product is stable for 12 months.
VOC classification (Directive 2004/42 / EC)	: EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC