

TRANSPARENT - COLORED SATIN WATER-BASED IMPREGNANT

SATIN WAXY WATER-BASED ACRYLIC FINISH

Characteristics	Impregnated transparent and colored protective water-based finish, for professional use, based on particular acrylic resins. Suitable for the definitive protection of chalets, matchboarding, fixtures, doors, fences, attics and in general for any internal or external wooden cladding. Compared to thixotropic finishes, application by brush and roller is easy, in spray applications it is advisable to apply thinner layers. It leaves no lapping defects.
Field of use	: Particularly designed for brush application on manufactured articles where a softness to the touch and an effect similar to there was.
Color	: Transparent - colored
Binder	: Acrylic
Specific weight	: about 1,000 - 1,050 kg/lt
Viscosity	: 25 cup Ford 4
Dilution	: With water, 2 to 5%
Application	: Mohair roller, flat brush with synthetic fibers for water-based enamels, spray equipment. Clean equipment with water immediately after use
Drying	: Dry to the touch after about 3 hours; cold and high humidity increase the drying time. Overlayability after 5 – 7 hours. Do not apply at temperatures below +10°C and with air humidity above 75%.
Surrender	: 5 - 7 square meters with 1 litre (2 hands)
Storage	: The product must be stored in its original containers, protected from frost and at a minimum temperature of + 5°C and max + 35°C. The product has a stability of 12 months.



21042 CARONNO PERTUSELLA (Va) – Via Trieste 285 – Tel. 029650607 – Fax 029659754

www.lakplaster.it – email: info@lakplaster.it

DATA SHEET

**VOC classification : EU limit value for this product (Cat.A/a): 30 g/l (2010)
(Directive 2004/42/EC) : This product contains a maximum of 30 g/l of VOC**