



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - email: info@lakplaster.it

DATA SHEET

SCENIPLASTER Scenography painting

Characteristics :Special opaque water-based water-based paint for scenography and exhibition stands.

Sceniplaster colors are particularly lively, they keep their original shades despite exposure to artificial light sources. It leaves no lapping defects.

Jobs : For scenographies and exhibitions, advertising signs and similar jobs that

require particular resistance duration.

Principles of photocatalysis: In the formula thanks to the use of titanium dioxide which is subjected to the rays

the molecules of polluting substances are transformed into substances harmless to

health and the process is also activated in the presence of artificial light.

Binder : Acrylic in water emulsion.

Pigments : Non toxic according to EEC standards

I wait : Opaque

Washability : After 48 hours. Over 10,000 flawless brush strokes

Specific weight : 1,250 - 1,650 kg / lt

Viscosity at 20°C: 13,500 - 16,000

: <u>By brush: dilution with water 30% at 9 m2/lt 2 coats</u>

By roller: dilution with water 30% at 9 m2/lt 2 coats
By spray: dilution with water 40% at 16 m2 /lt 1 coat

Colors : White and colored

Drying : To the touch : 40

: Stackability minutes : 6 hours

VOC classification : EU limit value for this product (Cat.A/a): 30 g/l (2010) (Directive 2004/42/EC): This product contains a maximum of 30 g/l of VOC