



Lak Plaster®
PITTURE E VERNICI



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

IDROLAK

MULTI-PURPOSE WATER-BASED ENAMEL FOR INTERIOR EXTERIOR

Features

IDROLAK is an enamel based on synthetic acrylic resins, dilutable with water, resistant to atmospheric agents, particularly suitable for painting wooden supports, concrete, fiber cement walls, rigid PVC, iron. IDROLAK stands out for its high resistance to bad weather, is permanently elastic, does not yellow, is resistant to light, particularly odorless, it is easily applied, dries quickly so that if necessary up to three coats a day can be applied. IDROLAK complies with the EURO EN 71 standard "toy safety" and with the "DIN 53 160" standard, resistant to saliva and sweat.

Field of use

: All supports in wood, iron, concrete, walls, fiber cement, (after adequate preparation), rigid PVC, toys.

Aesthetic effect

: IDROLAK is available in glossy / satin (about 20 gloss) / matt (about 8 gloss) versions

Viscosity at 20 ° C

4000 - 6000

Specific weight

: About 1,200 - 1,250 depending on the color

Dilution

: With water, 0 to 8%

Application

: Mohair roller, flat brush with synthetic fibers for water-based enamels, spray equipment. Clean equipment with water immediately after use

Drying

: Touch dry, after about 2 hours; cold and high humidity increase the drying time.
Do not apply at temperatures below + 10 ° C and with air humidity above 75%.

Binder

Acrylic

Surrender

: 7 - 8 square meters with 1 liter (2 coats)



21042 CARONNO PERTUSELLA (Va) - Via Trieste 285 - Tel. 029650607 - Fax 029659754

www.lakplaster.it - e-mail: info@lakplaster.it

DATA SHEET

VOC classification
(Directive 2004/42 / EC)

: EU limit value for this product (Cat A / a): 30 g / l (2010): This product contains a maximum of 30 g / l VOC